

Cold water high pressure washers

PW-C23



Standard accessories



TBAP40107
8 m H.P. hose



IPPR40012
Gun with athermic extension




LCPR40080 (IDAF94224)
LCPR40079 (IDAF94227)
Turbo nozzle



LCPR40076 (IDAF94224)
LCPR40074 (IDAF94227)
Lance with adjustable
head

Features

- Immediate total stop (the machine goes off automatically when the trigger gun is released)
- Axial pump with aluminium alloy head
- Stainless steel pistons with excellent mechanical characteristics
- Electric induction motor, two pole continuous duty. Maintenance free
- The motor is protected from excessively high temperatures by a thermal cutout
- Standard support for gun, lance and lance with rotating nozzle to have them ready to be used
- The starting handgrip, the detergent tap and the inlet water connection are placed on the front side of the machine
- Standard professional hose reel where it is possible to wind easily and rapidly the hose in order to protect it from any damage (IDAF94227)




Thanks to the particular chemical injection system and the two tanks of this machines, it is possible to deliver and adjust the quantity of two different detergents.



With a simple lever placed next to the hose reel, the hose can be blocked at the desired length.



Thanks to electric cable reel, it is possible to rewind the feeding cable when working operations are finished.



Code	Model	Remote control	Pressure (bar)	Flow rate (l/h)	Voltage (Ph-V-Hz)	Absorbed power (kW)	Max water inlet temp. (°C)	Hose (m)	Electric cable (m)	Weight (kg)	Dimensions (cm)
IDAF94224	PW-C23 I 1508 A-M	Total Stop	150	500	1-230-50	2.5	50	8	5	21,6	38x33x84
IDAF94227	PW-C23 P 1610 A-M	Total Stop	160	600	1-230-50	3	50	8	5	23	38x33x84